

New electronic shower panel
DL 400 E SENSOR

rada

PRESTO®
loves water

DL 400

Energy & water saving.
Durability you can count on.
Supports compliance management.

DL 400 SE®
Mechanical self-closing shower

DL 400 E SENSOR
Sensor touchless shower

SENSOR | TIMED-FLOW | PROGRAMMABLE

Modern and slim design
Non visible fixings, slim panel and anti-fingerprint finish

Robustness and reliability
- Product designed and tested for intensive use: 500 000 cycles minimum
- Salt spray resistant for outdoor use

Unparalleled comfort
Adjustable swivel showerhead with excellent spray pattern

Easy maintenance
- 42 rub-clean nozzles providing an easy to clean anti-limescale spray plate
- Light weight shower panel for ease of installation

PRODUCT CODES

Rada code	Description
41733	27403 – PRESTO DL400SE PANEL MECH
41734	27477 – PRESTO DL400E PANEL SENSOR BATTERY POWERED
41735	27479 – PRESTO DL400E PANEL SENSOR MAINS POWERED

SPECIFICATIONS

- Shower panel for pre-mixed or cold water
- Automatic stop after 30 sec.
- Flow rate: DL400SE – 10L/min flow rate. DL400E sensor – 6L and 8L/min flow limiter
- Water inlet: G1/2" with stop valve or G3/4" without stop valve
- Connection from the top with straight stop valve

BENEFITS



DL 400 SE® anti-blocking
Soft push and anti-vandalism

- Ergonomic button suitable for elderly and disabled people
- Patented anti-blocking system S® to avoid continous flow



DL 400 E SENSOR
Maximised savings and hygiene

- Electronic touchless Start/Stop function suitable for elderly and disabled people
- Flow duration, automatic rinsing and usage data can be set or downloaded via PRESTOCOM tool

PREVENTING LEGIONELLA
Automated duty flushing of showers helps to reduce the risk of water stagnation in pipework and bacterial proliferation (Legionella, Pseudomonas).

PRESTO®
loves water

COMFORT AND ANTI-SCALDING SECURITY

In order to guarantee a constant temperature and to avoid any risk of burn, equip your sanitary system with a thermostatic mixing valve. In case of cold water shut-off, hot water supply is shut-off immediately.



PESM0620J
RADA MEYNELL 15/3
½" point of use thermostatic mixing valve



1.0.407.06.3
RADA 215-T3 DK
½" thermostatic mixing valve



1.1847.013
RADA 320 IC
Thermostatic mixing valve incorporating

THE PRESTO TIP!

Water savings... but not only that!

Only one DL 400 E TOUCH® is enough!

If you have several DL 400 SE® installed in series, only one single DL 400 E TOUCH® installed at the end of the network will allow you to purge your entire water network!

Rada Controls
Kohler Mira Limited
Cromwell Road
Cheltenham
Gloucestershire
GL52 5EP

Telephone:
0344 571 1777

Email:
radacustomerservices@radacontrols.com

Web:
www.radacontrols.com

Linkedin:

Website: